

eCANTER 6S15e

LEFT-HAND DRIVE

MODEL / VEHICLE TYPE	6S15e			
----------------------	-------	--	--	--

Cab type / crew	Standard, single cab / 3			
Battery variant	S			M
Model variant	84004212	84004312	84004512	84005512
FUSO model code	FEAVKBLCSEU1	FEAVKCLCSEU1	FEAVKELCSEU1	FEAVKELDSEU1

DIMENSIONS [MM]				
-----------------	--	--	--	--

Wheelbase		2500	2800	3400
Overall length		4766	5044	5788
Cab length		1510		
Width overall		1876		
Cab width		1695		
Height overall		2160–2237	2159–2238	2157–2246
Track width	Front / rear	1390 / 1435		
Frame height (at end of frame)		150		
Ground clearance		260		
Cab to rear axle		1975	2279	2879
Cab to end of frame		3128	3478	4278
Maximum body length ²⁾		3500	3995	4985
Frame width		701		
Front overhang		993		
Rear overhang		1145	1195	1395
Front axle to front of body		625		
Recommended distance cab to body		100		


WEIGHTS [KG]				
--------------	--	--	--	--

Empty weight ¹⁾		2595	2605	2630
	Front / rear	1510 / 1085	1535 / 1070	1555 / 1075
Gross vehicle weight		6000		
Technical axle loads ¹⁾	Front / rear	2600 / 4500		
Chassis load bearing capacity ²⁾		3405	3395	3370

DRIVING PERFORMANCE AND AGILITY				
---------------------------------	--	--	--	--

Maximum speed	km/h	89		
Minimum turning circle [m]	Kerb to kerb	9.8	10.8	12.8
	Wall to wall	10.8	12.0	14.0

¹⁾ The weight refers to the base vehicle (European series, including high voltage battery, tyre sealant, tools and driver with 75 kg) without optional equipment. If any optional equipment is added, the weight changes accordingly.
²⁾ Calculated maximum value which should be checked depending on the body and application.
 Subject to change without notice. All data is approximate.



eCANTER 6S15e

LEFT-HAND DRIVE

110 kW (150 hp)
430 Nm

ELECTRIC DRIVE

Type	S40		
Peak output / continuous output	110 kW (150 hp) / 85 kW (116 hp)		
Maximum torque / continuous torque	430 Nm / 250 Nm		
PTO (optional)	Type	mPTO for pump connection	mPTO for pulley
	Maximum torque	222 Nm at 2000 rpm	64 Nm at 7000 rpm
	Continuous power / torque	17 kW / 166 Nm, maximum 2000 rpm	17 kW / 46 Nm, maximum 7000 rpm
	Gear ratio	0.286	–

HIGH VOLTAGE BATTERY

Battery variant	S		M
Capacity usable / installed	kWh	39 / 41	78 / 82
Weight ³⁾	kg	475	950
Range ⁴⁾	km	70	140

CHARGING

Connection type / variants	CCS TYP 2 (AC / DC)		
Maximum charging capacity AC / DC	kW	11 / 70	22 / 104
Maximum charging time AC ⁵⁾	0–100 % h:min	4:12	4:54
Maximum charging time DC ⁵⁾	20–80 % h:min	0:24	0:26
	5–90 % h:min	0:36	0:44

POWERTRAIN

Climbing ability	20 %
------------------	------

CHASSIS

Front axle / rear axle	Independent suspension / E-axle		
Tyres	205/75 R 17.5		
Wheel	17.5 x 6.00 - 115		
Steering	Left-hand drive	Recirculating ball steering with power assist, tilting telescopic steering column with steering-wheel lock	
Brake	Service brake	Hydraulic with vacuum power assist, dual-circuit with load-dependent brake proportioning valve at rear wheels	
	Front / rear	Disc brake (293 x 40 mm / 314 x 35 mm)	
	Parking brake	Electromechanical brake caliper on rear disc brake	
Suspension	Front / rear	Coil springs with shock absorber / Semi-elliptic leaf springs with shock absorber and stabilizer	
Frame	Type	Ladder-type frame with reinforcements and crossmembers	
Electrical system	Low voltage batteries	Series 12 V (80 Ah), optional 24 V (80 + 60 Ah)	

3) The specified weight includes both the battery(ies) with 325 kg each and the peripheral installations (cabling, temperature control, protection, etc.).

4) The range depends on various factors such as load, driving style, topography, ambient temperature or weather, battery age, vehicle equipment. The actual range may vary.

The given values for the range were tested with a box body, a load of 50 % of the payload, an ambient temperature of 20 °C and an average battery age.

5) The charging time depends on various factors such as the charging capacity of the vehicle and charging station, the battery's state of charge, ambient and battery temperature.

The given values for the charging time were tested under optimum ambient temperature of 20 °C.

The illustrations may contain accessories and items of optional equipment which are not part of the standard specification. The data sheet may contain product types and support services not available in certain countries.